

## **Gemini Deep Concave Q40**

**Manufacturer: Zaun Limited**

**Web:               www.zaun.co.uk**

**Tel:                +44 (0)1902 796699**

### **Product reference:**

Gemini Deep Concave Clamp.

### **Height:**

[ \_\_\_\_\_ ] - 0.830–6.0 m, insert requirements.

### **Horizontal wire thickness:**

[6 mm].

[8 mm].

### **Fixing:**

[Bolt down].

[In ground].

[Wall].

### **Gates:**

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

**Ball finials:**

[Not required].

[Required].

**Guidance for Gemini Deep Concave Clamp from Zaun Limited**

More about Gemini Deep Concave Clamp: As standard

As standard

**Finish:**

Galvanized and polyester powder coated.

**Mesh:**

Duo6 mesh comprising 50 x 200 mm mesh with two horizontal wires at 200 mm centres and single 6 mm vertical wires at 50 mm centres.

**Posts:**

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

**Post to panel fixing:**

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 400 mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

**Gates:**

# ZAUN

Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.