

Zariba 8 Plus Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

Zariba 8 Plus Clamp.

Height:

[_____] - 0.6–2.4 m in 200 mm increments, insert requirements.

Fixing:

[Bolt down].

[In ground].

[Wall].

Colour:

[_____] - Various available, consult manufacturer and insert requirements.

Feature top:

[As drawing]. - Consult manufacturer for available options.

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Guidance for Zariba 8 Plus Clamp from Zaun Limited

More about Zariba 8 Plus Clamp: As standard

As standard

Finish:

Galvanized and polyester powder coated.

Mesh:

Duo8 mesh comprising 200 x 50 mm mesh with single 6 mm vertical wires at 50 mm centres and dual 8 mm horizontal wires at 200 mm centres.

Posts:

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

Post to panel fixing:

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 400 mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

Gates:

Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.