









DualGuard

Applications:

-  Civic & Public Sector
-  Health & Emergency Services
-  High Security
-  Industrial
-  Residential & Commercial
-  Schools & Education
-  Transport & Infrastructure
-  Utilities

Drawings:

Download our drawings direct
from our website:

[www.zaun.co.uk/about-
us/downloads/drawings/](http://www.zaun.co.uk/about-us/downloads/drawings/)



Features & Benefits:

- A strong and rigid design, difficult for intruders to penetrate
- Difficult to climb with 25mm aperture
- Open mesh pattern providing a vandal resistant fence line
- Visually appealing perimeter fencing solution
- Provides high visibility for security and potential threats
- Premium twin wire product
- Available either bolt down, in ground or on wall

Description:

Zaun's **DualGuard** is one of the most heavyweight mesh systems available. **DualGuard** combines anti-climb mesh, incredible strength and great style to provide a perimeter fencing solution that is not only a deterrent but provides a greater level of security to the standard Duo8 range.

Derived from Zaun's Duo8 system, **DualGuard** combines twin 8mm horizontal wires with a high frequency of vertical wires to make an extremely robust 25mm x 200mm mesh pattern. The close mesh makes cutting or climbing the panel extremely difficult, yet the panel remains stylish and unobtrusive, enhancing the area in which it is situated. As a low level fence **DualGuard** acts as an attractive segregating barrier capable of withstanding heavy impacts.

The **DualGuard** system uses an anti-climb, tight mesh pattern and a full length clamp bar to cover the panel ends. This ensures that there are no exposed panel edges on which people might snag themselves and also makes levering the panels away from the post very difficult.

Details:

Minimum height of 630mm to maximum height of 6.0 metres – DualGuard Perimeter Fencing

Mesh:

DualGuard mesh comprising 25mm x 200mm mesh with dual 8mm horizontal wires at 200mm centres and single 6mm vertical wires at 25mm centres

Posts:

Various RHS posts sizes dependent on height (see chart below for details), spaced at 2525mm centres

Post to panel fixing:

Panels fixed to posts with full height 40mm x 5mm clamp bar with bolt fixings at 400mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

Gates:

Pedestrian gates are single leaf 1.2m wide, (or width to suit), framed in a 50mm x 50mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and 2 x suitable gate posts.

Vehicle access gates are double leaf (single leaf vehicle gates available) 3.0m wide (or width to suit), framed in 50mm x 50mm RHS, with Zaun Duo8 mesh welded inside the frame, with drop bolts and slide latch. Gate supplied with rubber bump stop and 2 x suitable gate posts.

Finish:

Materials are galvanised and Polyester Powder coated.

Drawings:

www.zaun.co.uk/about-us/downloads/drawings/

Specifications:

Height	Post Centres	Vertical Wires	Horizontal Wires	Mesh Pattern	Post Section
630mm to 1.80 mtr	2.525 mtr	6mm	8mm	25mm x 200mm	60mm x 40mm
2.00 mtr to 3.00 mtr	2.525 mtr	6mm	8mm	25mm x 200mm	80mm x 40mm
3.20 mtr to 4.00 mtr	2.525 mtr	6mm	8mm	25mm x 200mm	100mm x 50mm
5.00 mtr to 6.00 mtr	2.525 mtr	6mm	8mm	25mm x 200mm	120mm x 60mm

Technical Support

Should you require any help or assistance in your requirement please contact

sales@zaun.co.uk or

call +44 (0)1902 796 699

Turnkey Solutions

Zaun can provide you with solutions to suit all of your sport and perimeter protection requirements, whether you need to protect a school playground or a military base, Zaun has the solutions for you. From perimeter and sports fencing to CCTV and access control, Zaun can provide solutions to your specific requirements.

For more information on any of our products or services please visit our website at:
www.zaun.co.uk