









Duo6 Clamp

Features & Benefits:

- Designed with twin 6mm horizontal wires
- Open mesh pattern provides high visibility to monitor sites without restriction
- High level of vandal resistance
- Available with optional V-Beam to further increase strength
- Supplied with standard or minimal projections at the top of the panel
- Available either bolt down, in ground or on wall
- For low level fences a safety capping is available



Applications:

-  Civic & Public Sector
-  Health & Emergency Services
-  High Security
-  Industrial
-  Residential & Commercial
-  Schools & Education
-  Transport & Infrastructure
-  Utilities

Drawings:

Download our drawings direct from our website:

www.zaun.co.uk/about-us/downloads/drawings/

Description:

Zaun's **Duo6** twin wire perimeter fencing is our most popular fencing system, combining a perfectly engineered robust design with a low visual impact that will blend into any situation. **Duo6** is manufactured from dual horizontal 6mm wires sandwiching a single 5mm vertical wire, producing a 50mm x 200mm mesh pattern that is not only strong and vandal resistance but also offers the best value. **Duo6** is widely specified in both private and public sectors and has proven itself time and again.

The **Duo6** system uses a full length clamp bar to cover the panel ends ensuring there are no edges exposed on the panel on which people might snag themselves and also makes levering the panels away from the post extremely difficult.

Details:

Minimum height of 630mm to maximum height of 6.0 metres – Duo6 Perimeter Fencing

Mesh:

Duo6 mesh comprising 50mm x 200mm mesh with dual 6mm horizontal wires at 200mm centres and single 5mm vertical wires at 50mm centres

Posts:

Various RHS posts sizes dependent on height (see chart below for details), spaced at 2525mm centres

Post to panel fixing:

Panels fixed to posts with full height 40mm x 5mm clamp bar with bolt fixings at 400mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

Gates:

Pedestrian gates are single leaf 1.2m wide, (or width to suit), framed in a 50mm x 50mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and 2 x suitable gate posts.

Vehicle access gates are double leaf (single leaf vehicle gates available) 3.0m wide (or width to suit), framed in 50mm x 50mm RHS, with Zaun Duo8 mesh welded inside the frame, with drop bolts and slide latch. Gate supplied with rubber bump stop and 2 x suitable gate posts.

Finish:

Materials are galvanised and Polyester Powder.

Drawings:

www.zaun.co.uk/about-us/downloads/drawings/

Specifications:

Height	Post Centres	Vertical Wires	Horizontal Wires	Mesh Pattern	Post Section
630mm to 2.23 mtr	2.525 mtr	5mm	6mm	50mm x 200mm	60mm x 40mm
2.43 mtr to 3.68 mtr	2.525 mtr	5mm	6mm	50mm x 200mm	80mm x 40mm
3.88 mtr to 4.48 mtr	2.525 mtr	5mm	6mm	50mm x 200mm	100mm x 50mm
5.00 mtr to 6.00 mtr	2.525 mtr	5mm	6mm	50mm x 200mm	120mm x 60mm

Technical Support

Should you require any help or assistance in your requirement please contact

sales@zaun.co.uk or

call +44 (0)1902 796 699

Turnkey Solutions

Zaun can provide you with solutions to suit all of your sport and perimeter protection requirements, whether you need to protect a school playground or a military base, Zaun has the solutions for you. From perimeter and sports fencing to CCTV and access control, Zaun can provide solutions to your specific requirements.

For more information on any of our products or services please visit our website at:

www.zaun.co.uk