

## Duo6V Q40

**Manufacturer:** Zaun Limited

**Web:** [www.zaun.co.uk](http://www.zaun.co.uk)

**Tel:** +44 (0)1902 796699

## Product reference:

Duo6V.

## Height:

[ \_\_\_\_\_ ] - 0.630–6.0 m, insert requirements.

## Fixing:

[Bolt down].

[In ground].

[Wall].

## Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

## Safety capping:

[Not required].

[Required].

**Projection:**

[Minimal].

[Standard].

**Guidance for Duo6V from Zaun Limited**

More about Duo6V: As standard

As standard

**Finish:**

Galvanized and polyester powder coated.

**Mesh:**

Duo6V mesh comprising 50 x 200 mm mesh with dual 8 mm horizontal wires at 200 mm centres and single 6 mm vertical wires at 50 mm centres.

**Posts:**

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

**Post to panel fixing:**

Panels fixed to posts with ZaunFix fixing clips and bolt fixings at 400 mm centres.

**Gates:**

Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.