



Duo8 Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

[Duo8 Clamp].

[Duo8 Zaunfix].

Height:

[_____] - 0.630–6.0 m, insert requirements.

Fixing:

[Bolt down].

[In ground].

[Wall].

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Safety capping:

[Not required].

[Required].

Security rating:

[Not required].

[SR1]. - Consult manufacturer for details.

Projection:

[Minimal].

[Standard].

Guidance for Duo8 from Zaun Limited

More about Duo8: As standard - Options

As standard

Finish:

Galvanized and polyester powder coated.

Mesh:

Duo8 mesh comprising 50 x 200 mm mesh with dual 8 mm horizontal wires at 200 mm centres and single 6 mm vertical wires at 50 mm centres.

Posts:

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

Post to panel fixing:

ZAUN

- Clamp:

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 400 mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

- Zaunfix:

Panels fixed to posts with ZaunFix clip and bolt fixings at 400 mm centres.

Gates:

Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.

Options

Security rating:

SR1: Opportunist attack by bodily force using minimal tools (screwdriver, knife, pliers, etc.).