

Gemini Surf Q40 Manufacturer: Zaun Limited Web: www.zaun.co.uk Tel: +44 (0)1902 796699 **Product reference:** Gemini Surf Clamp. Height: [_____] - 0.830–6.0 m, insert requirements. **Horizontal wire thickness:** [6 mm]. [8 mm]. Fixing: [Bolt down]. [In ground]. [Wall]. Gates: Pedestrian:

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

[Not required].

[Not required].

Vehicular:



[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Ball finials:

Gates:

[Not required].
[Required].
Guidance for Gemini Surf Clamp from Zaun Limited
More about Gemini Surf Clamp: As standard
As standard
Finish:
Galvanized and polyester powder coated.
Mesh:
Duo6 mesh comprising 200 x 50 mm mesh with single 6 mm wires, vertical wires are at 50 mm centres, dual horizontal wires at 200 mm centres.
Posts:
Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.
Post to panel fixing:
Panels fixed to posts with full height 40×5 mm clamp bar with bolt fixings at 400 mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.



Framed in a $50 \times 50 \text{ mm}$ RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.