

Manufacturer: Zaun Limited Web: www.zaun.co.uk Tel: +44 (0)1902 796699 **Product reference:** Product reference: Duo6 Sports Spectator Rail. Height: [_____] - 1.0–1.2 m, insert requirements. Fixing: [Bolt down]. [In ground]. [Wall]. Gates: Pedestrian: [Not required]. [Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements. Vehicular: [Not required]. [Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Spectator Rail with Duo6 Sports Q40



Guidance for Spectator Rail with Duo6 Sports from Zaun Limited

More about Duo6 Sports Spectator Rail: As standard
As standard
Finish:
Galvanized and polyester powder coated.
Mesh:
Duo6 mesh comprising 50 x 200 mm mesh with single 5 mm vertical wires at 50 mm centres and dual 6 mm horizontal wires at 200 mm centres.
Posts:
60 x 60 mm rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.
Post to panel fixing:
Panels fixed to posts with full height 40×5 mm clamp bar with bolt fixings at 200 mm centres with EPDM inserts. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.
Gates:
Framed in a $50 \times 50 \text{ mm}$ RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.