

Manufacturer: Zaun Limited Web: www.zaun.co.uk Tel: +44 (0)1902 796699 **Product reference:** [Zariba 8 Clamp]. [Zariba 8 Zaunfix]. Height: [_____] - 0.6–2.4 m in 200 mm increments, insert requirements. Fixing: [Bolt down]. [In ground]. [Wall]. **Colour:** [_____] - Various available, consult manufacturer and insert requirements. Finials: [Not required]. [Required]. - Consult manufacturer for options. **Gates:**

Zariba 8 Q40

Pedestrian:



[Not required].
[Required] Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements
Vehicular:
[Not required].
[Required] Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.
Guidance for Zariba 8 from Zaun Limited
More about Zariba 8: As standard
As standard
Finish:
Galvanized and polyester powder coated.
Mesh:
Duo8 mesh comprising 200 x 50 mm mesh with single 6 mm wires, vertical wires are at 50 mm centres, dual 8 mm horizontal wires at 200 mm centres.
Posts:
Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.
Post to panel fixing:
- Clamp:
Panels fixed to posts with full height 40×5 mm clamp bar with bolt fixings at 400 mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

- Zaunfix:



Panels fixed to posts with ZaunFix clip and bolt fixings at 400 mm centres.

Gates:

Framed in a $50 \times 50 \text{ mm}$ RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.