

## Manufacturer: Zaun Limited Web: www.zaun.co.uk Tel: +44 (0)1902 796699 **Product reference:** Duo8 Sports Lite. Height: [\_\_\_\_\_] - 0.630–6.0 m, insert requirements. Fixing: [Bolt down]. [In ground]. [Wall]. Gates: Pedestrian: [Not required]. [Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements. Vehicular: [Not required]. [Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert

**Duo8 Sports Lite Q40** 

requirements.



Projection:
[Minimal].
[Standard].
Guidance for Duo8 Sports Lite from Zaun Limited
More about Duo8 Sports Lite: As standard
As standard
Finish:
Galvanized and polyester powder coated.
Mesh:
Duo8 mesh comprising 50 x 200 mm mesh with dual 8 mm horizontal wires at 200 mm centres and
single 6 mm vertical wires at 50 mm centres.
Posts:
Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.
Post to panel fixing:
Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 400 mm centres with
EPDM inserts. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.
Gates:
Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate
supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.
arop ports.