

Certificate of Product Approval

Certificate Number: 1164i

Issue: 01

Zaun Limited

Steel Drive
Wolverhampton
WV10 9ED

is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

Product

HiSec 358
security gates

Standard

LPS 1175: Issue 8
Requirements and testing procedures for the LPCB approval and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for BRE Global Ltd.

Paul Dillon
Verifier

2 December 2019
Date of Issue

2 December 2019
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX
T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



bre

Appendix to Certificate No: 1164i Zaun Limited

Issue: 01

Security Gates

Product Name	Type	Nominal Height (m)	Minimum Nominal Clear Opening Width (m)	Maximum Nominal Clear Opening Width (m)	Security Rating	LPCB Ref. No.
HiSec 358	Single leaf inward opening padlockable hinged gate with base-plated posts	2.07	1.0	1.585	A1 (SR1)	1164i/01
		2.47				
	Single leaf inward opening padlockable hinged gate with buried ('in ground') posts	2.075	1.0	1.585		
		2.475				
	Double leaf inward opening padlockable hinged gate with base-plated posts	2.47	2.0	3.135		
		3.07				
		2.475	3.2	5.135		
		3.075				
		2.48	5.0	7.135		
		3.08				
	Double leaf inward opening padlockable hinged gate with buried ('in ground') posts	2.475	2.0	3.105		
		3.075				
		2.475	3.2	5.105		
		3.075				
		2.475	5.0	7.105		
		3.075				

Compatible Locking Device

Manufacturer	Model	Type	Compatible Cylinder
Squire	SS50S	Padlock with open shackle	Squire 6-pin

Notes:

1. The nominal height of the gate is measured above the ground.
2. The nominal clear opening width is measured between the faces of the two gate posts.
3. The gate must be mounted onto flat topography and the local ground onto/into which the gate is installed must offer compatible strength.

This certificate and appendix is maintained and held in force through regular surveillance activities

P. Dillon

Signed for BRE Global Ltd.

Paul Dillon
Verifier

2 December 2019
Date of Issue

2 December 2019
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX
T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



bre

Appendix to Certificate No: 1164i Zaun Limited

Issue: 01

Alternative Sales Address:

Binns Fencing Limited

Harvest House
Cranborne Rd
Potters Bar
Hertfordshire
EN6 3JF
Tel: +44 (0)1707 855555

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for BRE Global Ltd.

Paul Dillon
Verifier

2 December 2019
Date of Issue

2 December 2019
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX
T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.

