

HiSec SR1 Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

HiSec SR1.

Height:

[_____] - 2.0–2.4 m.

Width:

[_____] - 3.0 m maximum.

Fixing:

[Bolt down].

[In ground].

[Wall].

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Security rating:

[Not required].

[SR1]. - Single Fix only. Consult manufacturer for details.

Guidance for HiSec SR1 from Zaun Limited

More about HiSec SR1: As standard - Options

As standard

Finish:

Galvanized and polyester powder coated.

Mesh:

HiSec SR1 mesh comprising of 12.7 x 76.2 mm mesh with single 4 mm vertical wires at 76.2 mm centres and 4 mm horizontal wires at 12.7 mm centres.

Posts:

60 x 40 mm or 80 x 40 mm rectangular hollow section (RHS) 2750 mm or 3100 mm m long for fixing in ground 670 mm and spaced at a maximum of 3025 mm centres.

Post to panel fixing:

Panels fixed to posts with full height 40 x 5 mm clamp bar with stainless steel fixings at 400 mm centres.

Gates:

Framed in a 50 x 50 mm RHS with Zaun HiSec mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.

Options

Security rating:

SR1: Opportunist attack by bodily force using minimal tools (screwdriver, knife, pliers, etc.).