

HiSec Profile Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

HiSec V Profile Spider.

Height:

[_____] - 0.6–5.2 m.

Width:

[_____] - 3.0 m maximum.

Fixing:

[Bolt down].

[In ground].

[Wall].

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Guidance for HiSec V Spider from Zaun Limited

More about HiSec V Spider: As standard

As standard

Finish:

Galvanized and polyester powder coated.

Mesh:

HiSec V beam mesh comprising 12.7 x 76.2 mm mesh with 4 mm vertical wires at 76.2 mm centres with 4 mm horizontal wires at 12.7 mm centres.

Posts:

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

Post to panel fixing:

Panels fixed to posts with spider clips with bolt fixings at 400 mm centres.

Gates:

Framed in a 50 x 50 mm RHS, with Zaun HiSec mesh bolted onto the frame using the Zaun picture frame design, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.