



HiSec Super SR2 Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

HiSec Super SR2.

Height:

[_____] - 2.0–5.2 m, insert requirements.

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Guidance for HiSec Super10 SR2 from Zaun Limited

More about HiSec Super10 SR2: As standard

As standard

Finish:

Galvanized and polyester powder coated.

**Mesh:**

HiSec Super10 mesh comprising of 76.2 x 12.7 mm mesh with single 10 mm vertical wires at 76.2 mm centres and 4 mm horizontal wires at 12.7 mm centres.

Posts:

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

Post to panel fixing:

Panels fixed to posts with full height 80 x 5 mm clamp bar with twin stainless steel bolt fixings at 400 mm centres. The full height clamp bars create a safe finish with the mesh ends behind the clamp bar.

Gates:

Framed in 100 x 50 mm RHS, with Zaun HiSec Super mesh bolted onto the frame using the Zaun picture frame design, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.