

Surface Mount Blocker

Features & Benefits:

- Impact tested to BSI PAS 68:2010
- Road surface blocker - no foundations
- Can also be installed flush with ground
- Hydraulically operated 400V
- 100% duty rating
- Instantly reversible
- Width up to 4 metres (securing apertures of 5.8m)
- Concertina safety skirt to prevent potential trapping areas



Description:

The Terror Stopper PAS 68 Surface Mount Blocker, successfully impact tested to BSI PAS 68: 2010 specification and remains bolted in its original position during and after impact.




Using surface mount technology the PAS 68 blocker ensures that the installation requires no foundations (a flush mount installation is also available). The concertina skirt also ensure that there are no potential trapping areas.

Successfully impact tested to PAS 68 stopping a 7.5 tonne N3 vehicle travelling at 50 mph (80kph) and on impact the blocker stopped the vehicle within the aperture.

Hydraulically driven and designed for ease of installation and maintenance. The Terror Stopper PAS 68 Surface Mount Blocker also capable interfacing to any access control system. Also including a traffic light system as standard.

A surface mounted blocker successfully impact tested and rated to PAS 68 V/7500[N3]/80/90:0.0/7.6.

Applications:

-  Industrial
-  Transport & Infrastructure
-  Utilities
-  Construction
-  High Security

Drawings:

Download our drawings direct from our website:

www.zaun.co.uk/about-us/downloads/drawings/

Details:

PAS 68 Classification Code: V Road Blocker/7500[N3]/80/90:0.0/7.6

Height: Lift Height 1100mm

Width: Variable up to 4000mm (securing apertures of 5800mm)

Axle Loadings: 30 tons

Construction: The blocking segment shall be constructed of heavy steel section with steel front plate and covers

Finish: Shotblasted, hot zinc sprayed (galvanised), primed and finished with a final coat of polyurethane paint. Special Lifetime Paint; an anti-slip paint for road vehicles available on request.

Options: Accumulator - allows a number of operations in power failure mode, EFO(Extra Fast Operation), Manual Hand pump, High Security Cabinet, Anti-tamper alarms

Safety: Vehicle Detector Loops, Safety Photocells, LED Traffic light heads, Flashing beacon, Audible alarm

Normal Operating Speed/Time: 4-6 seconds

Depending on configuration

EFO Speed: Up to 1 second

Depending on configuration

Duty Cycle: 100% duty rating

Durability: Fully functional after PAS 68 impact test

Controls: The programmable logic controller (PLC) with built in safety features will accept inputs from access control systems including access card, voice, etc. Push button as supplied as standard

Drawings:

www.zaun.co.uk/about-us/downloads/drawings/

Technical Support

Should you require any help or assistance in your requirement please contact

sales@zaun.co.uk or

call +44 (0)1902 796 699

Turnkey Solutions

Zaun can provide you with solutions to suit all of your sport and perimeter protection requirements, whether you need to protect a school playground or a military base, Zaun has the solutions for you. From perimeter and sports fencing to CCTV and access control, Zaun can provide solutions to your specific requirements.

For more information on any of our products or services please visit our website at:

www.zaun.co.uk